



STANDALONE PROXIMITY READERS

PROXIMITY READERS



SPX-26P



SPX-26M



SPECIFICATION

SPX-26P / SPX-26M

- IP66
- Voltage: 12VDC
- Temp: -40 to +60C
- Current consumption: 410mA
- 2000 users
- Output time 1-99 seconds
- Read range 3-10cm
- Lock output load 2amp

SPX-26M

- Vandal resistant
- Tri colour LED

FEATURES

SPX-26P / SPX-26M

- Built in anti tamper (LDR)
- Buzzer for audible or silent mode
- Read 125KHz 26 bit EM cards or fobs
- Remote infrared programmer / or Master cards
- LED status display

Use with the following fobs:

- KP-FOB (Grey or Blue)
- KP-CARD
- KP-HD-CARD

OTHER PRODUCTS

FIREISO1



AS900-M



DIMENSIONS

SPX-26P

- 102x48x20 (mm)
- 100g (Boxed)

SPX-26M


- 102x48x20 (mm)
- 240g (Boxed)

CONTENTS

SPX-26P / SPX-26M

- 1 x Reader
- 1 x Infrared Remote Control
- 1 x Master add card
- 1 x Master delete card
- 1 x Diode

ML600



DHM600-60



Manufactured by a BSIA Member